

ULTRA FLUORO IMPREGNATING TILE & STONE SEALER – TDS

Product Name:

Ultra Fluoro Impregnating Tile & Stone Sealer.

Product description:

Ultra Fluoro Impregnating Tile & Stone Sealer is a hybrid system with fluorocarbon technology based sealer which bonds with tile/ stone for improved wear resistance. It penetrates into porous stones/ tiles. It provides a natural look with maximum protection against the toughest oil & water based stains, wine, vinegar, pickle, sambar coke, ink etc., are the kind of stains, it can resist. The low odor formula makes it easy to use with a durable long lasting seal. The sealed area provides a breathable surface in exteriors & interiors. It also allows moisture vapor transmission and inhibits the growth of mould and mildew.

Advantages:

- Natural look and Protects against UV rays
- Hydrophobic/ oleophobic
- Allows tiles / stones to breathe
- Protects against toughest oil & water based stains
- Durable long lasting Seal
- Improved wear resistance & non yellowing

Area of usage:

- Interiors & exteriors
- Wall & floor
- Marble & flamed Granite
- Lime stone, sand stone, Terrazzo & slate
- Porous tiles, grouted joints & vitrified tiles

Application Method:

- Ensure the surface is clean where the sealer is to be applied and also free from loose particles.
- Apply neatly the sealer on the Tile / Stone using a soft bristle brush. Leave it to soak for 5 minutes and wipe any excess sealer remaining on the Tile / Stone.
- Allow 30 minutes of drying time between coats. Apply one or more coat

as necessary depending on the porosity of the Tile / Stone.

- Allow it to dry for 12 hours before laying the tile/stone is used for trafficking.

NOTE: Do not use sealer in damp condition.

Packing:

1 ltr & 5 ltr

Storage:

Fluoro Impregnating Tile/ Stone Sealer has a shelf life of 12 months in original unopened container. Store in dry conditions between 5 C and 30 C, protect from direct sunlight.

Precaution:

Keep out of reach of children. Wear suitable protective clothing, gloves and eyes/face protection. After contact with skin, wash immediately with plenty of clean water. In case of contact with eyes rinse immediately with plenty of clean water and seek medical advice.

Technical Data:

Appearance	Transparent liquid
Shelf life	12 months
Specific Gravity	1.220 to 1.225 at 30°C
Chloride content	Nil to IS:456
Coverage	10 – 25m ²

Corporate office:

ULTRA GREEN CONSTRUCTION CHEMICALS

#42, 2nd main road
 Palace Guttahalli main road
 Near Vinayaka circle
 Bangalore – 560003
 Ph: 080-65344500
 E-mail: info@ultragreenc.com
 Web: www.ultragreenc.com

