

## ULTRA GLOSSY SEALER - TDS

### Product name:

Ultra Glossy Sealer

### Product description:

Ultra Glossy Sealer is solvent based deep penetrating sealer designed for use on marble, lime stone, granite, slate, terrazzo and other natural stone to reduce the water permeability of the surface. It can be used on both wall and floor tiles. It reduces stains, seals with a wet look finish enhancing the colour of the tiles, provides a breathable surface in interior and exterior tiled surfaces.

### Advantages:

- Seals with a wet look finish
- Stain resistant
- Non-yellowing
- Improves wear resistant of tile and stones
- Reduces water permeability
- Enhances the colour of the tile.

### Application method:

- Make sure the surface is clean.
- After cleaning rinse with clean water and allow the surface to dry completely up to 2 - 3 days.
- Treat the surface with ultra Glossy sealer with soft bristled brush and leave it to soak for few minute and remove the excess sealer from surface if any.
- Allow at least 2 hours for the surface to dry before second coat.
- Apply additional coats depending upon the porosity of the Tile / stone.
- Allow the treated surface for foot traffic after 24 hours of application of final coat.

### Limitations:

- Do not allow sealer to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form. If this occurs, clean with scrub pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

### Precautions:

Do not mix with other products like detergent, acid etc., keep away from children. Avoid contact to eye or skin. In case of accidental contact with eye or skin

flush with water at least 15 minutes. If irritation persists, seek medical attention. If swallowed do not induce vomiting drink 1 or 2 glasses of water or milk. Seek medical help immediately and show the container to the doctor. Use rubber gloves while handling.

### Storage:

- Close container tightly after each use. Store in original container only.
- Store and use between temperatures of 45 degree F - 85 degree F.
- Keep only in the original container and store upright in cool place.

### Area of application:

- Interior and Exterior
- Floor and Wall
- All kind of Natural stone and tiles

### Packing:

1 ltr

### Technical Data:

Appearance	Transparent liquid
Shelf life	12 months
Working Temperature	5 degree C - 45 degree C
Stain resistant	Excellent
Specific Gravity	0.998 g/cc
Approx.Coverage	10 - 25 m2*
Foot traffic	24 hours

\*Depending on porosity of the substrate.

### Corporate office:

#### ULTRA GREEN CONSTRUCTION CHEMICALS

#42, 2<sup>nd</sup> main road  
Palace Guttahalli main road  
Near Vinayaka circle  
Bangalore - 560003  
Ph: 080-65344500  
E-mail: [info@ultragreenc.com](mailto:info@ultragreenc.com)  
Web: [www.ultragreenc.com](http://www.ultragreenc.com)

