

ULTRA NANO SEALER - TDS

Product name:

Ultra Nano Sealer

Product description:

Ultra Nano Sealer is a hybrid system with fluorochemical technology based sealer, which bonds with tile / stone for improved wear resistance. And it deeply penetrates into porous effective of Vitrified and Nano tiles. It provides a natural look with maximum protection against the toughest oil & water based stains, wine, vinegar, pickle, sambar, coke, ink etc., are the kind of stains, it can resist. The low odour formula makes it easy to use with a durable long lasting seal. The sealed area provides a breathable surface in exteriors & interiors. It also allows moisture vapour transmission and inhibits the growth of mould.

Advantages:

- Natural look and Protects against UV rays
- Hydrophobic/ oleophobic
- Allows tiles / stones to breath
- Protects against toughest oil & water based stains
- Durable long lasting Seal
- Improved wear resistance & non yellowing

Application method:

- Make sure the surface is clean.
- After cleaning rinse with clean water and allow the surface to dry completely up to 2 - 3 days.
- Treat the surface with ultra Nano sealer with soft bristled brush and leave it to soak for few minute and remove the excess sealer from surface if any.
- Allow at least 2 hours for the surface to dry before second coat.
- Apply additional coats depending upon the porosity of the Tile / stone.
- Allow the treated surface for foot traffic after 24 hours of application of final coat.

Limitations:

- Do not allow sealer to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form. If this occurs, clean with scrub pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

Precautions:

Do not mix with other products like detergent, acid etc., keep away from children. Avoid contact to eye or skin. In case of accidental contact with eye or skin flush with water at least 15 minutes. If irritation persists, seek medical attention. If swallowed do not induce vomiting drink 1 or 2 glasses of water or milk. Seek medical help immediately and show the container to the doctor. Use rubber gloves while handling.

Storage:

- Close container tightly after each use. Store in original container only.
- Store and use between temperatures of 45 degree F - 85 degree F.
- Keep only in the original container and store upright in cool place.

Area of application:

- Interior and Exterior
- Floor and Wall
- All kind of Natural stone and tiles

Packing:

1 ltr.

Technical Data:

Appearance	Transparent liquid
Shelf life	12 months
Working Temperature	5 degree C - 45 degree C
Stain resistant	Excellent
Specific Gravity	0.98 g/cc
Approx.Coverage	10 - 25 m2*
Foot traffic	24 Hours

*Depending on porosity of the substrate.





ULTRA NANO SEALER - TDS

Corporate office:

ULTRA GREEN CONSTRUCTION CHEMICALS

#42, 2nd main road
Palace Guttahalli main road
Near Vinayaka circle
Bangalore – 560003
Ph: 080-65344500
E-mail: info@ultragreenc.com
Web: www.ultragreenc.com

