

ULTRA SEALER- TDS

Product Name:

Ultra Sealer

Product description:

Ultra sealer is water based deep penetrating sealer for tiles and stones to reduce water permeability of the surface. High resistance to water and alkali stains it is ideal for interior and exterior use, it exhibits a glossy finish with maximum protection against stains.

Advantages:

- Stain resistance
- High wear resistance for porous tiles
- Breathable /Glossy finish

Application Method:

- Make sure the surface is clean.
- After cleaning rinse with clean water and allow the surface to dry completely up to 24 hours.
- Treat the surface with ultra sealer with soft bristled brush and leave it to soak for few minute and remove the excess sealer from surface if any.
- Allow at least 2 hours for the surface to dry before second coat.
- Apply additional coats depending upon the porosity of the Tile / stone.
- Allow the treated surface for foot traffic after 24 hours of application of final coat.

Limitations:

- Do not allow sealer to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form. If this occurs, clean with scrub pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

Precautions:

Do not mix with other products like detergent, acid etc., keep away from children. Avoid contact to eye or skin. In case of accidental contact with eye or skin flush with water at least 15 minutes. If irritation persists, seek medical attention. If swallowed do not induce vomiting drink 1 or 2 glasses of water or milk. Seek medical help immediately and show the container to the doctor. Use rubber gloves while handling.

Storage:

- Close container tightly after each use. Store in original container only.
- Store and use between temperatures of 45 degree F - 85 degree F.

- Keep only in the original container and store upright in cool place.

Packing:

500 ml, 5 ltr.

Technical Data:

Appearance	Milky white liquid
Shelf life	12 months
Working Temperature	5 degree C - 45 degree C
Stain resistant	Excellent
pH	7 - 8.5
Specific Gravity	1.01 g/cc
Approx. Coverage	10 - 25 m2*
Foot traffic	24 hours

*Depending on porosity of the substrate.

Corporate office:

ULTRA GREEN CONSTRUCTION CHEMICALS

#42, 2nd main road
 Palace Guttahalli main road
 Near Vinayaka circle
 Bangalore - 560003
 Ph: 080-65344500
 E-mail: info@ultragreenc.com
 Web: www.ultragreenc.com

