

## ULTRA WET LOOK SEALER – TDS

### Product Name:

**Ultra** Wet Look Sealer

### Product description:

**Ultra** wet look sealer is solvent based enhancer for tiles and stones, to reduce water permeability of the surface. High resistance to water and alkali stains it is ideal for interior and exterior use, it exhibits a wet look finish.

### Advantages:

- Stain resistance
- High wear resistance for porous tiles
- Breathable /wet look finish

### Application Method:

- Make sure the surface is clean.
- After cleaning rinse with clean water and allow the surface to dry completely up to 24 hours.
- Treat the surface with ultra wet look sealer with soft bristled brush and leave it to soak for few minute and remove the excess sealer from surface if any.
- Allow at least 2 hours for the surface to dry before second coat.
- Apply additional coats depending upon the porosity of the Tile / stone.
- Allow the treated surface for foot traffic after 24 hours of application of final coat.

### Limitations:

- Do not allow sealer to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form. If this occurs, clean with scrub pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

### Precautions:

Do not mix with other products like detergent, acid etc., keep away from Children. Avoid contact to eye or skin. In case of accidental contact with eye or skin flush with water at least 15 minutes. If irritation persists, seek medical attention. If swallowed do not induce vomiting drink 1 or 2 glasses of water or milk. Seek medical help immediately and show the container to the doctor. Use rubber gloves while handling.

### Storage:

- Close container tightly after each use. Store in original container only.
- Store and use between temperatures of 45 degree F – 85 degree F.
- Keep only in the original container and store upright in cool place.

### Packing:

1 ltr.

### Technical Data:

Appearance	Transparent liquid
Shelf life	12 months
Working Temperature	5 degree C – 45 degree C
Stain resistant	Excellent
Specific Gravity	0.991 g/cc
Approx. Coverage	10 – 25 m2*
Foot traffic	24 hours

\*Depending on porosity of the substrate.

### Corporate office:

#### ULTRA GREEN CONSTRUCTION CHEMICALS

#42, 2<sup>nd</sup> main road  
 Palace Guttahalli main road  
 Near Vinayaka circle  
 Bangalore – 560003  
 Ph: 080-65344500  
 E-mail: [info@ultragreenc.com](mailto:info@ultragreenc.com)  
 Web: [www.ultragreenc.com](http://www.ultragreenc.com)

### ULTRA GREEN CONSTRUCTION CHEMICALS

Survey No-11, Bandahalli Village, Byllanarasapura Road, Nandagudi Hobli Hostoke Taluk, Bangalore-562122

Tel : 080-65344500 E-mail: [info@ultragreenc.com](mailto:info@ultragreenc.com) [ultragreenconstructionchemical@gmail.com](mailto:ultragreenconstructionchemical@gmail.com)

Web: [www.ultragreenc.com](http://www.ultragreenc.com)

